

From: Sepulvado, Murry R  
Sent: Tue Apr 13 20:32:26 2010  
To: Morel, Brian P; Sepulvado, Ronald W  
Cc: Guide, John  
Subject: RE: Rev 1 Procedure  
Importance: Normal

Base oil sounds good to me.

Murry R. Sepulvado  
Well Site Leader  
Transocean Deepwater Horizon  
Office 281-366-7741 or 7742  
Dispatcher 281-366-7743

---

**From:** Morel, Brian P  
**Sent:** Tuesday, April 13, 2010 2:47 PM  
**To:** Sepulvado, Ronald W; Sepulvado, Murry R  
**Cc:** Guide, John  
**Subject:** RE: Rev 1 Procedure

I will add details to the program. Currently my thoughts are negative testing with base oil to the mud line, you both ok with that?

---

**From:** Sepulvado, Ronald W  
**Sent:** Tuesday, April 13, 2010 3:54 AM  
**To:** Morel, Brian P; Sepulvado, Murry R  
**Cc:** Guide, John  
**Subject:** RE: Rev 1 Procedure

Brian

We need to do a negative test before displacing 14# mud to seawater, will have to pick a time to lay down some drill pipe, should only need 3600' of 6 5/8" 32# drill pipe and 3400' of 5 1/2" 21.9# HT-55 for the Nile Well. We have 188 stands. of 5 1/2" 21.9#, 6 5/8" 32# S-135, 6 5/8" 40# S-135 and 6 5/8" 40# V-140 in the derrick.

Ronnie

**From:** Morel, Brian P  
**Sent:** Monday, April 12, 2010 12:57 PM  
**To:** Sepulvado, Murry R; Sepulvado, Ronald W  
**Cc:** Guide, John  
**Subject:** Rev 1 Procedure

This isn't perfect yet, but I wanted to get everyone a copy so you can ensure all the equipment required for our upcoming operations is offshore in time. Please let me know if you have any questions or suggestions how to

improve the procedure.

Thank You,  
Brian Morel