

Initial EDS in system

 <b>CAMERON CONTROLS</b>	DRAWN BY Richard Coronado	REVISION C01	<b>X-201259-21</b>
	DATE June 22, 2000	SHEET 1 of 8	

**EMERGENCY DISCONNECT SEQUENCES,**

**MUX BOP CONTROL SYSTEM**

**FOR**

**"DEEPWATER HORIZON"**

**R & B FALCON**

**CHECKED BY:**

\_\_\_\_\_  
Print Name:

\_\_\_\_\_  
Date

**APPROVED BY:**

\_\_\_\_\_  
Print Name

\_\_\_\_\_  
Date

**CUSTOMER  
APPROVED BY:**

\_\_\_\_\_  
Print Name:


\_\_\_\_\_  
Date

This document contains confidential and trade secret information which is the sole property of CAMERON, a division of COOPER CAMERON CORPORATION. Receipt or possession does not convey any right to loan, sell or otherwise disclose said information. Reproduction or use of said information for any purpose other than that for which it is intended may not be made without written permission from CAMERON. This document is to be returned to CAMERON upon request and in all events upon completion of the use for which it is intended.

<p>5173</p> <hr/> <p>Exhibit No. _____</p> <p><b>Worldwide Court Reporters, Inc.</b></p>
--


5/7/2010 8:38:40 AM SAP-CORONADO X-201259-21-001-00-00-CURRENT\_C01.P10.TIF

PROPERTY OF  <b>CAMERON CONTROLS</b>	DRAWN BY Richard Coronado	REVISION C01	<b>X-201259-21</b>
	DATE June 22, 2000	SHEET 2 of 8	




5/7/2010 8:38:40 AM SAP-CORONADO X-201259-21-001-000-00-CURRENT\_CCP100.TIF

PROPERTY OF  <b>CAMERON CONTROLS</b>	DRAWN BY Richard Coronado	REVISION C01	<b>X-201259-21</b>
	DATE June 22, 2000	SHEET 3 of 8	



5/7/2010 8:38:40 AM SAP-CORONADO X-201259-21-001-00-00-CURRENT\_CCP100.TIF

PROPERTY OF  <b>CAMERON CONTROLS</b>	DRAWN BY Richard Coronado	REVISION C01	X-201259-21
	DATE June 22, 2000	SHEET 4 of 8	



5/7/2010 8:38:40 AM SAP-CORONADO X-201259-21-001-00-00-CURRENT\_CCP100.TIF

PROPERTY OF  <b>CAMERON CONTROLS</b>	DRAWN BY Richard Coronado	REVISION C01	<b>X-201259-21</b>
	DATE June 22, 2000	SHEET 5 of 8	

#### 4.0 EDS1 Sequence

To initiate the "EDS1" Sequence, simultaneously press the "ENABLE" button and the RED "EDS" button on either the Driller's or Toolpusher's control panels.

The following FDS Sequence will be used for Drill Pipe or "Normal"

Time (sec)	Function	Operation
0 sec		
1 sec		
5 sec		
18 sec		

This document contains confidential and trade secret information which is the sole property of CAMERON, a division of COOPER CAMERON CORPORATION. Receipt or possession does not convey any right to loan, sell or otherwise disclose said information. Reproduction or use of said information for any purpose other than that for which it is intended may not be made without written permission from CAMERON. This document is to be returned to CAMERON upon request and in all events upon completion of the use for which it is intended.

5/7/2010 8:38:40 AM SAP-CORONADO X-201259-21-001-00-00-CURRENT-CP10.TIF



PROPERTY OF



**CAMERON  
CONTROLS**

DRAWN BY  
Richard Coronado

REVISION  
C01

DATE  
June 22, 2000

SHEET  
7 of 8

X-201259-21

### 5.0 EDS2 Sequence

To initiate the "EDS2" Sequence, simultaneously press the "ENABLE" button and the RED "EDS" button on either the Driller's or Toolpusher's control panels.

The following EDS Sequence will be used for Casing Shear

Time (sec)	Function	Operation
0 sec		
1 sec		
5 sec		
25 sec		
43 sec		

This document contains confidential and trade secret information which is the sole property of CAMERON, a division of COOPER CAMERON CORPORATION. Receipt or possession does not convey any right to lease, sell or otherwise disclose said information. Reproduction or use of said information for any purpose other than that for which it is intended may not be made without written permission from CAMERON. This document is to be returned to CAMERON upon request and in all events upon completion of the use for which it is intended.

5/7/2010 8:38:40 AM SAP-CORONADO X-201259-21-001-000-CURRENT.CCP100.TIF

PROPERTY OF 	DRAWN BY Richard Coronado	REVISION C01	X-201259-21
	DATE June 22, 2000	SHEET 8 of 8	

48 sec	
50 sec	
51 sec	

The following are approximate times and volumes @ 3000 psi:

Function	Operation	Time (seconds)	Volume (gallons)
		10	1
		13	25
		25	70
		3	2
		8	2
		8	2
		5	3
		5	1
		1	0.25
		8	0.50
		*	19 (includes Sec. Volume)

(Time and Volume included in Primary)

\* The LMRP Connector Primary/Secondary takes 8 seconds to Unlatch and 7 seconds to fully open position.  
Total time: 15 seconds

**ALL TIMES ARE APPROXIMATE AND CAN BE ADJUSTED TO EXACT TIMES AFTER STACK TESTING.**

This document contains confidential and trade secret information which is the sole property of CAMERON, a division of COOPER CAMERON CORPORATION. Receipt or possession does not convey any right to loan, sell or otherwise disclose said information. Reproduction or use of said information for any purpose other than that for which it is intended may not be made without written permission from CAMERON. This document is to be returned to CAMERON upon request and in all events upon completion of the use for which it is intended.

5/7/2010 8:38:40 AM SAP-CORONADO X-201259-21-001-00-00-CURRENT\_CP100.TIF