



- NOTES:
- IN ACCORDANCE WITH CAMERON SPECIFICATION X-254205-02
  - DATE CODE SHALL CONSIST OF FOUR DIGIT NUMBER FOLLOWED BY A SINGLE LETTER INDICATING MONTH, YEAR AND WEEK OF MANUFACTURE. EXAMPLE: 059000 = SEPTEMBER, 1990 4th WEEK
  - SERIAL NUMBER ASSIGNED BY OA.
  - CONTRACT NUMBER OR P.O. NUMBER ON WORK ORDER SUPPLIED BY CUSTOMER SERVICE.

NO LOAD VOLTAGE (OCV)		LOAD VOLTAGE (CCV)	
9.5 V MIN.	10.02 V MAX	8.3 V MIN.	8.5 V MAX
UNDE BREAKDOWN TEST			
1. COLD TO 41°C VOLTS FOR A MIN. OF 1 SEC. TO OBTAIN FULL SECTION			
2. MAXIMUM REVERSE CURRENT FLOW SHOULD NOT EXCEED 100 MILLIAMP.			

SAFT AMERICA INC.  
310 Crescent Street  
Wilmington, DE 19804  
Telephone: 800-874-0111  
Fax: 820-874-2431

DATE: 06/27/05  
REV: 1

DESCRIPTION: COOPER CAMERON BATTERY

SIZE: C  
QTY: 3933001200  
CASE: 76634

REVISIONS:

REV	DESCRIPTION	DATE
0	NEW ISSUE	12/11/04
1	ADDED NOTE 4, REMOVED HALF-Y DUTY ON DRAWING.	02/04/05
2	NO CHANGE THIS PAGE.	02/11/05
3	REVISED CONNECTOR VIEW	03/10/05
4	CHANGE LABEL LAYOUT	03/25/05
5	ADD PIN P/N & WIRE CALLOUTS.	04/15/05
6	ADDED "CAMERON P/N" TO LABEL.	04/27/05
7	100V TESTING MAX. WAS 9.9V.	07/13/05

3/20  
Exhibit No. \_\_\_\_\_  
Worldwide Court Reporters, Inc.

NOTES: UNLESS OTHERWISE SPECIFIED  
1. SEE BOM FOR MATERIAL SPECIAL REQUIREMENTS.  
2. IDENTIFY PART FOR (102)

151, WIL 1185

DO NOT SCALE

DATE: 06/27/05

REV: 1

SAFT AMERICA INC. CAMERON

BATTERY PACK, 5VDC, 41A/HR

JIMMIE W. WALLEY

224288-01

5K-154449-01