

HALLIBURTON

Cementing Gulf of Mexico, Broussard

LAB RESULTS - Primary

Job Information

Request/Slurry	73909/2	Rig Name	TRANSOCEAN HORIZON	Date	April 12th 2010
Submitted By	Jesse Gagliano	Job Type	9 7/8" X 7" Prod Casing	Bulk Plant	Fourchon-C-Port I, La, USA
Customer	BP	Location	Mississippi Cny	Well	Mississippi Canyon 252 OCS-G-32306 Macondo #1

Well Information

Casing/Liner Size	7"	Depth MD	18360 ft	BHST	210 F
Hole Size	9 7/8"	Depth TVD	18360 ft	BHCT	135 F

Drilling Fluid Information

Mud Company	MI	Type	SOBM	Density	14,1 PPG	PV/YP
-------------	----	------	------	---------	----------	-------

Cement Information - Primary Design

Conc	UOM	Cement/Additive	Sample Type	Sample Date	Lot No.	Cement Properties	
						Slurry Density	16.741 PPG
						Slurry Yield	1.37 FT3
100.00	% BWOC	Lafarge Class H	Rig	Apr 05, 2010	Tank # 8	Water Requirement	4.93 GPS
						Total Mix Fluid	5.02 GPS
0.07	% BWOC	EZ-FLO	Rig	Apr 05, 2010		Foam Density	14.496 PPG
0.25	% BWOC	D-Air 3000	Rig	Apr 05, 2010		Foam Quality	12.98 %
1.88	lb/sk	KCl (Potassium Chloride) Salt	Rig	Apr 05, 2010		Water Source	Fresh Water
20.00	% BWOC	SSA-1 (Silica Flour) - PB	Rig	Apr 05, 2010		Water Chloride	N/A ppm
15.00	% BWOC	SSA-2 (100 Mesh) - PB	Rig	Apr 05, 2010			
0.20	% BWOC	SA-541	Rig	Apr 05, 2010			
0.11	gps	ZoneSealant 2000	Lab	Mar 15, 2009			
0.09	gps	SCR-100L	Lab	Oct 22, 2009	6264		
4.93	gps	Fresh Water	Lab	Apr 12, 2010	FRESH WATER		

Operation Test Results Request ID 73909/2

Thickening Time, Request Test ID:812338

Temp (°F)	Pressure (psi)	Reached in (min)	Start BC	30 Bc (hh:mm)	40 Bc (hh:mm)	50 Bc (hh:mm)	70 Bc (hh:mm)
135	14,458	83	14	07:25	07:34	07:36	07:37

Mud Balance Density, Request Test ID:811529

Density (ppg)

16.7

from part 1

Mixability (0 - 5) - 0 is not mixable, Request Test ID:811524

Mixability rating (0 - 5)

4

This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

UCA Comp. Strength, Request Test ID:811522

End Temp (°F)	Pressure (psi)	50 psi (hh:mm)	500 psi (hh:mm)	12 hr CS (psi)	24 hr CS (psi)	48 hr CS (psi)
210	14,458	08:12	08:40	2,301	2,966	3,099

Circulate before pouring C.S. for 3 Hrs

Operation Test Results Request ID 73909/1**Crush Compressive Strength, Request Test ID:806069**

Curing Temp (°F)	Time 1 (hrs)	Strength 1	Time 2 (hrs)	Strength 2	Time 3 (hrs)	Strength 3	Foam quality
180	12	0	24	0	48	1,590	0

Condition for 1.5 hrs

FYSA Viscosity Profile & Gel Strength, Request Test ID:806074

Test Temp (°F)

80

600=14, 300=7, 200=5, 100=3, 60=1, 30=1, 6=1, 3=1.... 6D=1, 3D=1

Non API Rheology, Request Test ID:806075

Test temp (°F)	600	300	200	100	60	30	20	10	6	3
80	180	84	56	28	26	8	6	4	2	2

Non API Rheology, Request Test ID:806076

Test temp (°F)	600	300	200	100	60	30	20	10	6	3
135	130	56	40	20	12	8	6	4	4	2

Foam Mix and Stability, Request Test ID:813603

Time to Foam [Sec]	SG top	SG bot.	Conditioning time (hrs:min)
8	1.8	1.8	03:00

This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.