



ENGINEERING REPORT ABSTRACT

REPORT NUMBER: 3495

DATED: 11/13/2007

SUBJECT: Shear Test Using 18-15M TL CDVS Rams on 10 3/4" C110 60.7 ppf Casing

ABSTRACT:

Using an 18-15M TL equipped with an ST-Lock tandem operator configuration, the CDVS rams successfully performed 3 shears on 10 3/4" C110 60.7 ppf Casing supplied by Schahin. The recorded shear pressures were 1996 PSI, 1834 PSI & 1847 PSI. After each shear test a low and high pressure test was successfully conducted on the BOP assembly.

AUTHOR: *J.P. Corkhill*
John Corkhill
Engineering Supervisor

APPROVED: *Manish Vyas*
Manish Vyas
Patent Manager

APPROVED: *Mel Whitby*
Mel Whitby
Senior Engineering Manager

APPROVED: *David McWhorter*
David McWhorter
Vice President of Engineering & Quality

INDEX CATEGORY: DRILLING

KEY WORDS: BOP, Shear, CDVS, Casing.

ER ABSTRACT CLASSIFICATION STATUS

— CONFIDENTIAL NOT CONFIDENTIAL

ER CLASSIFICATION STATUS

— CONFIDENTIAL PROPRIETARY

NOTES

1. "CONFIDENTIAL" ERs AND "CONFIDENTIAL" ER ABSTRACTS may be distributed only to the individuals listed on X-110861-08.
2. "PROPRIETARY" ERs may be distributed to Cameron employees only. Distribution outside of Cameron may be made only with written authorization by the Regional Director of Engineering. Division distribution is listed on X-110861-08.
3. "NOT CONFIDENTIAL" ER ABSTRACTS may be distributed to Cameron employees and to customers.

CAM-2017

